


NICHROME ON SILICON


Single Ended SCSI Termination Circuit Thin Film Resistor Networks

NEW PRODUCT



SCHEMATICS

Single Ended SCSI (Small Computer System Interface)
Termination Network



4

ELECTRICAL

Standard Resistance Range, Ohms	22 to 500
Operating Temperature Range	-55°C to +125°C
Interlead Capacitance	<2pF
Insulation Resistance	≥10,000 Megohms
Noise, Maximum (MIL-STD-202, Method 308)	-25dB
Maximum Operating Voltage	100Vdc or √PR

ENVIRONMENTAL

Thermal Shock plus Power Conditioning, Maximum	ΔR 0.1%
Moisture Resistance, Maximum	ΔR 0.1%
Mechanical Shock, Maximum	ΔR 0.1%
High Temperature Exposure, Maximum	ΔR 0.1%
Marking Permanency	per MIL-STD-202, Method 215
Storage Temperature Range	-55°C to +125°C

Specifications subject to change without notice.

MECHANICAL

Lead Plating	80/20 Tin Lead
Lead Material	Copper Alloy
Lead Configuration	Gull Wing
Lead Coplanarity	0.004" (0.102mm)
Substrate Material	Silicon
Resistor Material	Passivated Nichrome
Body Material	Molded Epoxy

TOLERANCES


Accuracy Code	F	G	J
Absolute Resistance Tolerances at 25°C	1.0%	2.0%	5.0%
Ratio Tolerances at 25°C	1.0%	N/A	N/A
Temperature Coefficient of Resistance			±100ppm/°C
Temperature Coefficient of Resistance, Tracking			±5ppm/°C

PACKAGE POWER, WATTS @ 70°C, MAX.

QSOP		SOIC (NARROW)	SOIC (WIDE)	
16	20	16	16	20
0.75	1.0	0.8	1.0	1.2

Power per resistor @ 70°C, Max. is 100mW, not to exceed package power.


POWER DERATING CURVE



OUTLINE DIMENSIONS

Refer to standard package Outline Dimensions at the end of the Model NiCr on Si section.

ORDERING INFORMATION



4

CUSTOM SOLUTIONS

Networks designed to meet your specific electrical and packaging requirements are available.
Please contact the factory for technical assistance, price and availability.